



USB 2.0 Docking Station

Model No. : DK201, DK202



DK201

DK202



Features

1. Fully compliance with USB spec Ver.2.0 & Ver1.1
2. Tiered star topology supports up to 6 tiers and 127 devices and up to 5M USB cable provides stable transmission.
3. Bus-powered or self-powered by selection.
4. Per port over current detection, protection.
5. Auto detect the speed and connection of devices for each downstream port.
6. Plug and play capability for USB peripherals.
7. Support OHCI, UHCI & EHCI spec.
8. Support Windows 98 and Windows 98 SE, ME/2000/XP.

Specifications

Dimensions (LXWXH)	120 x 65 x 26mm
Unit Weight	120g
Cable Length	USB A/B type cable 1.8M
Connect Ports	USB, PS/2, RS-232 and Printer
USB Upstream port	X 1
USB Downstream port	USB 2.0 x 3, USB 1.1 x 1
Mini PS/2 port	X 2 (Keyboard, Mouse)
RS-232 port (DB-9)	X 1
IEEE-1284 Printer port (DB-25)	X 1
Compliant with USB version	USB 1.0/USB 1.1/USB 2.0
Compliant with HID version	USB HID 1.1
Over-Current protection	Yes
Bus-Power limit current protection	500mA (When external adaptor applied)
Power & Access LED indicator	Yes
Power	By host or external adaptor
Power Adaptor	DC 5V/2A (Optional)
OS Complies	Windows 98/98SE/ME/2000/XP