



4-Port USB KVM with Hub (OSD)

Model No. : KC141



Features

- Provides 4 USB upstream ports and VGA input to support the switching between 4 host PC.
- Complies with USB specification: 1.0/1.1
- Control 4PCs with one PS/2 Keyboard (or USB Keyboard) , One PS/2 mouse (or USB mouse) and one Monitor.
- Support 3 USB downstream ports (especially for sharing USB printers, USB storage, USB CD-RW etc..)
- Support 3 types of switching: Hardware push button, hot keys on PS2 Keyboard, and On-Screen-Display (OSD) Utility software (for Windows only)
- OSD functions include
 1. Display which host is plugged or which host is selected.
 2. Support Device detector to display USB downstream ports status.
- Support smart selection to automatically switch to an existing host when one active host is disabled.
- Support error alarm when the switching is improper.
- Support VGA resolutions up to 1920 x 1440
- Plug and Play. No software driver is needed for PS/2 mouse and Keyboard operation.
- Support the Force Switch function for VGA cable plugged only or to specify the host for booting procedure.
- Support Win 98/SE/ME/2000/XP;Linux/MAC/Sun Marco OSs.

Specification

Dimensions (LXWXH)	200 x 85 x 44mm
Unit Weight	720g
Cable Length	1.8M x 4
Connect Ports	USB, VGA, PS/2
USB Upstream port	X 4
USB Downstream port	USB 1.1 x 3
VGA Input port	X 4
VGA Output port	X 1
Mini PS/2 port	X 2 (Keyboard, Mouse)
Working PC selection	Push Button/Hot key/OSD(Optional)
PC selection button	X 4
Compliant with USB version	USB 1.0/USB 1.1
Compliant with HID version	USB HID 1.1
Video Resolution	2048 x 1536 (Max.)
Auto Scan	Yes
Auto Switch	Yes
Over-Current protection	Yes
Power & Working LED indicator	Yes
Working PC status indicator	X 4
VGA status indicator	X 4
Power	By host or external power adaptor
Power Adaptor	DC 5V/2A (Optional)
OS Complies	Windows 98/98SE/ME/2000/XP, Mac OS9/X, Linux, Sun Micro OS