



## 2-Port Combo KVM Switch

Model No. : KCB-121



### Advantages

**Complex connections with PCs via PS/2 and/or USB arbitrarily.**

### Features

1. Controls 2 computers from a single console (Keyboard/Mouse) over PS/2 and/or USB connections.
2. Supports Windows, Linux, Mac OS9/OSX, Sun.
3. Emulates a keyboard on each PC to allow your computers to boot normally without a keyboard error.
4. Supports hot-swap. All devices connected to the KVM can be added or removed at any time, without shutting the unit down.
5. Supports 2 types of switching: (1) Hardware Push Button, (2) Hot-Keys on PS/2 keyboard.
6. Supports Auto-Scan function to alternate video between different computers in preset intervals.
7. Supports LED display for Selected and On-Line status monitoring.
8. Supports VGA resolutions up to 2048 x 1536 @ 85HZ.
9. Supports Beeper enabled/disable feature.
10. Self powered through PS/2 connection or USB connection.
11. Fully compliant with the USB 1.1/2.0 specification.

### Package Contents

1. 2-Port Combo KVM Switch .
2. User Manual.
3. Two sets of integrated ( 2 x PS/2 + USB + VGA ) cables.

### Specifications

Number Of Computers Controlled		2
Selection Method		Push Button and Hot-Key (PS/2 keyboard)
LEDs		Red for PC Selection Green for PC connected ready
PC Connectors	Video	1 x HDB-15 male ( PS/2 & USB signal combined )
Console Ports	Keyboard	1 x 6 pin mini-DIN female
	Mouse	1 x 6 pin mini-DIN female
	Video	1 x HDB-15 female
Auto-Scan Interval		From 5 to 250 Seconds
DDC, DDC2 monitor		Yes (Max. Resolution: 2048x1536)@85Hz
Hot Swappable		Yes
Operating systems supported		<b>Windows 98SE/ME/2000/XP/2003 Server, Linux Mac and Sun Micro Systems</b>
Device driver		No Need
Power		By PS/2 or USB or Power Adaptor (Optional)
Cable Length		6 feet (1.80 Meter)
Dimensions (L X W X H)		14 x 8.5 x 4.5 cm
Unit Weight		420 g
Housing material		Metal
Operating Temperature		32~ 122°F (0~ 50°C )
Humidity		0%~80%RH