



2-Port Combo Free (USB & PS/2) KVM Switch

Model No. : KCF-121



Advantages: (Patent No. TW M 284961)

1. **Console** your **Keyboard / Mouse** via **PS/2 and/or USB** arbitrarily.
2. **Complex** connections with **PCs** via **PS/2 and/or USB** arbitrarily.

Features

1. Controls 2 computers from a single console (Keyboard/Mouse) over PS/2 and/or USB connections.
2. Supports Windows, Linux, Mac OS9/OSX, Sun.
3. Emulates a keyboard on each PC to allow your computers to boot normally without a keyboard error.
4. Supports hot-swap. All devices connected to the KVM can be added or removed at any time, without shutting the unit down.
5. Supports 2 types of switching: (1) Hardware Push Button, (2) Hot-Keys on PS/2 and/or USB of keyboard.
6. Supports Auto-Scan function to alternate video between both computers in preset intervals.
7. Supports LED display for Selected and On-Line status monitoring.
8. Supports VGA resolutions up to 2048 x 1536 @ 85HZ.
9. Supports Beeper during Switching enabled.
10. Self powered through PS/2 and/or USB connection.
11. Fully compliant with the USB 1.1/ 2.0 specification.

Package Contents

1. 2-Port Combo Free KVM Switch .
2. User's Manual.
3. Two sets of integrated (2 x PS/2 + USB + VGA) cables.

Specifications

Number Of Computers Controlled	2	
Selection Method	Push Button and Hot-Key (PS/2 and/or USB Keyboard)	
LEDs	Red for PC Selection Green for PC On-Line ready	
PC Connectors	Video	1 x HDB-15 male (PS/2 & USB signal combined)
Console Ports	Keyboard	1 x 6 pin mini-DIN female
	Mouse	1 x 6 pin mini-DIN female
	Video	1 x HDB - 15 female
	Keyboard	1 x USB - A type female
	Mouse	1 x USB - A type female
Auto-Scan Interval	From 5 to 250 Seconds	
DDC, DDC2 monitor	Yes (Max. Resolution: 2048x1536)@85Hz	
Hot Swappable	Yes	
Operating systems supported	Windows 98SE/ME/2000/XP/2003 Server, Linux Mac OS9/OSX and Sun Micro System	
Device driver	No Need	
Power	By PS/2 and/or USB or Power Adaptor (Optional)	
Cable Length	6 feet (1.80 Meter)	
Dimensions (L X W X H)	14 x 8.5 x 4.5 cm	
Unit Weight	440 g	
Housing material	Metal	
Operating Temperature	32~ 122°F (0~ 50°C)	
Humidity	0%~80%RH	