



2-Port Combo Free (USB & PS/2) KVM Switch with Audio

Model No. : KCF-121A



Advantages: (Patent No. TW M 284961)

1. **Console** your **Keyboard / Mouse** via **PS/2 and/or USB** arbitrarily.
2. **Complex** connections **with PCs** via **PS/2 and/or USB** arbitrarily.

Features

1. Controls 2 computers from a single console (Keyboard/Mouse) over PS/2 and/or USB connections.
2. Supports Windows, Linux, Mac OS9/OSX, Sun.
3. Emulates a keyboard on each PC to allow your computers to boot normally without a keyboard error.
4. Supports hot-swap. All devices connected to the KVM can be added or removed at any time, without shutting the unit down.
5. Supports 2 types of switching: (1) Hardware Push Button, (2) Hot-Keys on PS/2 and/or USB of keyboard.
6. Supports Auto-Scan function to alternate video between both computers in preset intervals.
7. Supports LED display for Selected and On-Line status monitoring.
8. Supports VGA resolutions up to 2048 x 1536 @ 85HZ.
9. Supports Beeper during Switching enabled.
10. Self powered through PS/2 and/or USB connection.
11. Fully compliant with the USB 1.1/ 2.0 specification.
12. Enabled audio (Microphone/Speaker)

Package Contents

1. 2-Port Combo KVM Switch with Audio.
2. User's Manual.
3. Two sets of custom intergrated (2 x PS/2 + USB + VGA) and audio (mic&speaker) cables.

Specifications

| | | |
|--------------------------------|---|--|
| Number Of Computers Controlled | 2 | |
| Selection Method | Push Button and Hot-Key (PS/2 and/or USB Keyboard) | |
| LEDs | Red for PC Selection Green for PC connected ready | |
| PC Connectors | Video | 2 x HDB-15 male (PS/2 & USB signal combined) |
| | Audio | 2 sets (mic/speaker) |
| Console Ports | Keyboard | 1 x 6 pin mini-DIN female |
| | Mouse | 1 x 6 pin mini-DIN female |
| | Video | 1 x HDB-15 female |
| | Audio | 1 set (mic/speaker) |
| Auto-Scan Interval | From 5 to 250 Seconds | |
| DDC, DDC2 monitor | Yes (Max. Resolution: 2048x1536)@85Hz | |
| Hot Swappable | Yes | |
| Operating systems supported | Windows 98SE/ME/2000/XP/2003 Server, Linux Mac and Sun Micro Systems | |
| Device driver | No Need | |
| Power | By PS/2 or USB or Power Adaptor (Optional) | |
| Cable Length | 6 feet (1.80 Meter) | |
| Dimensions (L X W X H) | 14 x 8.5 x 4.5 cm | |
| Unit Weight | 440 g | |
| Housing material | Metal | |
| Operating Temperature | 32~ 122°F (0~ 50°C) | |
| Humidity | 0%~80%RH | |