



3-Port DVI COMBO FREE KVM SWITCH W/ Audio

Model No. : KCF131DA



Advantages: (Patent No. TW M 284961)

1. Console your Keyboard/Mouse via either way of PS/2 and/or USB arbitrarily.
2. Controls 3 DVI computers from a single console (Keyboard/Mouse) over USB connections.

Features

1. Console your Keyboard/Mouse via either way of PS/2 and/or USB arbitrarily.
2. Controls 3 DVI computers from a single console (Keyboard/Mouse) over USB connections.
3. Supports Windows, Linux, Mac OS9/OSX, Sun.
4. Emulates a keyboard on each PC to allow your computers to boot normally without a keyboard error.
5. Supports hot-swap. All devices connected to the KVM can be added or removed at any time, without shutting the unit down.
6. Supports 2 types of switching:
 - (1) Hardware Push Button,
 - (2) Hot-Keys on PS/2 and/or USB of keyboard arbitrarily.
7. Supports Auto-Scan function to switch video automatically among computers in preset intervals sequentially.
8. Supports LED display for PC status monitoring.
9. Supports DVI UXGA resolutions up to 1600 x 1200.
10. Supports Beeper during switching enabled.
11. Enabled audio (Mic / Speaker).
12. Self powered through PS/2 and/or USB connection.
13. Fully compliant with the USB 1.1/ 2.0 specification.

Package Contents

1. 3-Port DVI COMBO FREE KVM SWITCH W/ Audio.
2. User's Manual.
3. Three sets of custom (DVI, USB+2 x 3.5 mm audio) cables.

Specifications

| | | |
|--------------------------------|----------|--|
| Number Of Computers Controlled | | 3 |
| Selection Method | | Push Button and Hot-Key (PS/2 and/or USB Keyboard) |
| LEDs | | Red for PC Selection Green for PC On-Line ready |
| PC Connectors | USB | 3 x USB (type B) female |
| | Video | 3 x DVI UXGA female |
| | Audio | 3 sets (speaker / Mic) |
| Console Ports | Keyboard | 1 x 6 pin mini-DIN female |
| | Mouse | 1 x 6 pin mini-DIN female |
| | Video | 1 x DVI UXGA female |
| | Keyboard | 1 x USB - A type female |
| | Mouse | 1 x USB - A type female |
| | Audio | 3 sets (speaker / Mic) |
| Auto-Scan Interval | | From 5 to 250 Seconds |
| DDC, DDC2 DVI UXGA monitor | | Yes (Max. Resolution: 1600 x 1200) |
| Hot Swappable | | Yes |
| Operating systems supported | | Windows 98SE/ME/2000/XP/2003 Server, Linux Mac OS9/OSX and Sun Micro System |
| Audio | | Enabled (Mic / Speaker) |
| Power | | By PS/2 and/or USB or External Power Adaptor (Optional) |
| Cable Length | | 6 feet (1.80 Meter) |

| | |
|------------------------|--|
| Dimensions (L X W X H) | 21.5 x 8.8 x 4.5 cm (5.5 X 3 X 1.7 inches) |
| Unit Weight | 650 g |
| Housing material | Metal |
| Operating Temperature | 32~ 122°F (0~ 50°C) |
| Humidity | 0%~80%RH |