



USB to Serial (RS232) Adaptor

Model No. : US111



Features

Hardware Feature

- Single Chip USB---Asynchronous Serial Data Transfer.
- Full Handshaking & Modem Interface Signals.
- UART I/F Supports 7/8Bit Data, 1/2 Stop Bits and Odd/Even/Mark/Space/No Parity.
- Data rate 300-230k Baud.
- 384Byte Receive Buffer / 128Byte Transmit Buffer for high data throughput.
- Full hardware assisted hardware or X-on / X-Off handshaking.
- In-built support for event characters and line break condition.
- UHCI/OHCI/EHCI host controller compatible.
- USB 1.1 and USB 2.0 compatible.

Application Areas

- USB Smart Card Readers.
- PDA-USB data transfer.
- ISDN terminal adapter..
- Bar code scanner.
- USB Hardware Modem.

Specifications

Dimensions(L*W*H)	56*30*15mm
Unit Weight	60g
Cable Length	1.8M
Connect Ports	RS-232
RS-232 Ports(DB-9)	*1
Compliant with USB version	USB1.1/2.0
Automatic handshake mode	YES
Power & Access LED indicator	YES
Power	By host power
OS Complies	Windows98/98SE/ME/2000/XP,Mac OS9/X, Linux kernel 2.4.xx above